




Wasserdichte Kabelverschraubung aus PA66GF UL90 VO 960°C
 Waterproofed screwed cable gland, material PA66GV UL90 VO 960°C




max. 32 A	450 V~	5 Bar	T85	4mm ²
H05W-F				
Pole poles	min. min.	max. max.	Artikelnummer ref.-No.	
3	3G 1,5 mm ² Ø 5 mm	3G 4 mm ² Ø 13 mm	238-470-51	



max. 32 A	450 V~	5 Bar	T85	4mm ²
H05W-F				
Pole poles	min. min.	max. max.	Artikelnummer ref.-No.	
5	5G 1,5 mm ² Ø 8 mm	5G 4 mm ² Ø 17 mm	238-471-51	



max. 32 A	450 V~	5 Bar	T85	4mm ²
H05W-F				
Pole poles	min. min.	max. max.	Artikelnummer ref.-No.	
3	3G 1,5 mm ² Ø 5 mm	3G 4 mm ² Ø 13 mm	238-472-51	



max. 32 A	450 V~	5 Bar	T85	4mm ²
H05W-F				
Pole poles	min. min.	max. max.	Artikelnummer ref.-No.	
5	5G 1,5 mm ² Ø 8 mm	5G 4 mm ² Ø 17 mm	238-473-51	