

# LED 12V<sup>(DC)</sup>



prim. [input] : 95 - 260Vac / 50 - 60Hz  
 sec. [output] : 12V (DC), 12W  
 Abmessungen [dimensions] 120x32x22mm,  
 thermischer Schutz [thermal protection],  
 Kurzschlußschutz [short-circuit-protection]

**550-016-50**



prim. [input] : 230 V  
 Frequenz : 50 - 60 Hz  
 sec. [output] : 12V (DC), 12W  
 Abmessungen [dimensions] 103x67x30mm,  
**dimmbare** incl. Potentiometer 10kOhm  
**dimmbare** incl. potentiometer 10kOhm

**550-049-50**



prim. [input] : 230V  
 Frequenz : 50-60Hz  
 sec. [output] : 12V (DC) 4,2W  
 Abmessung [dimension] (LxBxH) 46x34x24mm  
 Überlastschutz [overload protection]  
 Kurzschlußschutz [short-circuit-protection]  
 Ausgang: Kabel 2000mm  
 [output: cable 2000mm]

**550-052-51**



prim. [input] : 230V  
 Frequenz : 50-60Hz  
 sec. [output] : 12V (DC) 10W  
 Abmessung [dimension] (LxBxH) 60x44x27mm  
 Überlastschutz [overload protection]  
 Kurzschlußschutz [short-circuit-protection]  
 Ausgang: Kabel 2000mm  
 [output: cable 2000mm]

**550-053-51**