




LED

power 350






50
54
55
58
59
70

Nennstrom [current] 230V	Nennleistung [rated power] 9 W	Verbindung [connection] 
	IP65	 Ø175xL260
CE	Type LED-Diode Luxeon Star 1W	Anzahl [quantity] LED 9
Netzgeräte [converter] incl.	optische Linse [optical lense] 10° 553-168-.. optische Linse [optical lense] 30° 553-170-..	



50
54
55
58
59
70




Nennstrom [current] 230V	Nennleistung [rated power] 9 W	Verbindung [connection] 
	IP65 max. 60cm	 Ø175xH350
CE	Type LED-Diode Luxeon Star 1W	Anzahl [quantity] LED 9
Netzgeräte [converter] incl.	optische Linse [optical lense] 10° 553-169-.. optische Linse [optical lense] 30° 553-171-..	

mit Zuleitung
[with cable] 5000mm



50
54
55
58
59
70

IP68
(max. 0,6m)

Nennstrom [current] 350 mA konstant	9 x Luxeon	9 W	Verbindung [connection] 
	IP68 (max. 0,6m)	 150	
	220	Netzgerät [converter] 350 mA	
CE	Unterwasser-Strahler aus Edelstahl, Gummikabel 5000mm [underwater lighting made of stainless steel, rubber cable 5000mm]		

optische Linse
[optical lense] 10° **553-869-..**
optische Linse
[optical lense] 30° **553-879-..**