

# LED power 350



(ØxH) 50x33mm

Farbe [colour]	Nennstrom [current]	Nennleistung [rated power]	Verbindung [connection]
50	350 mA konstant	3 W	
54	Type LED-Diode	Anzahl [quantity] LED	Netzgeräte [converter]
55	Luxeon	3	350 mA
58	Star		
59	Abstrahlwinkel Flood [wide beam]		
70	45°		
98			
Befestigungsplatte mit Mittelloch Ø 3,2 mm [fixing sheet with hole Ø 3,2 mm]			

**553-624-..**



(ØxH) 50x33mm

Farbe [colour]	Nennstrom [current]	Nennleistung [rated power]	Verbindung [connection]
50	350 mA konstant	3 W	
54	Type LED-Diode	Anzahl [quantity] LED	Netzgeräte [converter]
55	Luxeon	3	350 mA
58	Star		
59	Abstrahlwinkel Flood [wide beam]		
70	45°		
98			
Befestigungsplatte mit Mittelloch M8x1 [fixing sheet with hole M8x1]			

**553-625-..**



(ØxH) 50x26mm

Farbe [colour]	Nennstrom [current]	Nennleistung [rated power]	Verbindung [connection]
50	350 mA konstant	1 W	
54	Type LED-Diode	Anzahl [quantity] LED	Netzgeräte [converter]
55	Luxeon	1	350 mA
58	Star		
59	Spot-Linse ca. 10° [narrow beam about 10°]		
70			
Befestigungsplatte mit Lochung 2 x Ø 3,2 mm/19 mm [fixing sheet with 2 holes Ø 3,2 mm/19 mm]			

**553-635-..**



(ØxH) 50x26mm

Farbe [colour]	Nennstrom [current]	Nennleistung [rated power]	Verbindung [connection]
50	350 mA konstant	1 W	
54	Type LED-Diode	Anzahl [quantity] LED	Netzgeräte [converter]
55	Luxeon	1	350 mA
58	Star		
59	Flood-Linse ca. 30° [wide beam about 30°]		
70			
Befestigungsplatte mit Lochung 2 x Ø 3,2 mm/19 mm [fixing sheet with 2 holes Ø 3,2 mm/19 mm]			

**553-636-..**