

LED 12V^(DC)

Netzgeräte 12Vdc
power supplies 12Vdc

SELV  IP 66   CE

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	12 Vdc 30 W / 2,5A	Aluminium aluminium	212x37x27 mm	250 g	prim.+ sec.150mm	max. 50°C	550-073-00



SELV  IP 66   CE

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	12 Vdc 60 W / 5A	Aluminium aluminium	178x69x44 mm	800 g	prim. 200 mm sec. 2 x 200 mm	max. 50°C	550-074-00



SELV  IP 66   CE

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	12 Vdc 100 W 8,34 A	Aluminium aluminium	240x70x44 mm	1200 g	prim. 250 mm sec. 2 x 250 mm	max. 50°C	550-075-00



SELV  IP 66   CE

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	12 Vdc 150 W 12,5A	Aluminium aluminium	236 x 127 x 58 mm	2350 g	prim. 250 mm sec. 4 x 250 mm	max. 50°C	550-076-00

