

LED 12V^(DC)

Netzgeräte 12 Vdc
power supplies 12Vdc


SELV  IP 00  TÜV bauartgeprüft 

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ambient temperature	Artikel-nummer ref.-No.
88 - 264 Vac 50 - 60 Hz	12 Vdc 150 W / 12,5A	Metall metal	199x110x50mm	860 g	ohne without	max. 50°C	550-068-50




SELV  IP 20  M M 

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
220 - 240 Vac 50 - 60 Hz	12 Vdc 20 W / 1,66 A	Kunststoff plastic	145x55x19mm	130 g	ohne without	max. 50°C	550-039-50



SELV  IP 20  M M 

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable output	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
220 - 240 Vac 50 - 60 Hz	12 Vdc 20 W / 1,66 A	Kunststoff plastic	145x55x19mm	135g	150 mm Steckverbindung 12 Vdc 150 mm connector 12 Vdc	max. 50°C	550-039-60



SELV  IP 20  M M 

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable output	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
220 - 240 Vac 50 - 60 Hz	12 Vdc 20 W / 1,66 A	Kunststoff plastic	145x55x19mm	145g	150 mm mit 6-fach Verteiler 150 mm with 6 x distributor	max. 50°C	550-039-70

