

LED 24V_(DC)

Netzgeräte 24Vdc
power supplies 24Vdc

SELV   



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	24 Vdc 30 W / 1,25A	Aluminium aluminium	212x37 x 27 mm	250 g	prim.+ sec.150mm	max. 50°C	552-073-00

SELV   



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	24 Vdc 60 W 2,5A	Aluminium aluminium	178x69x44 mm	800 g	prim. 200 mm sec. 2 x 200 mm	max. 50°C	552-074-00

SELV   



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	24 Vdc 100 W 4,16 A	Aluminium aluminium	240x70x44 mm	1200 g	prim. 250 mm sec. 2 x 250 mm	max. 50°C	552-075-00

SELV   



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
170 - 250 Vac 50 - 60 Hz	24 Vdc 150 W 6,25 A	Aluminium aluminium	236 x 127 x 58 mm	2350 g	prim. 250 mm sec. 4 x 250 mm	max. 50°C	552-076-00