


LED 24V_{DC}

Netzgeräte 24 Vdc
power supplies 24 Vdc



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel prim./sec. cable prim./sec.	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
220-240 V / 50 - 60 Hz	24 Vdc 20 W / 0,833 A	Kunststoff plastic	145 x 55 x 19 mm	130 g	ohne without	max. 50°C	552-081-50



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel prim./sec. cable prim./sec.	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
90 - 264 V / 50 - 60 Hz	24 Vdc 60 W / 2,5 A	Kunststoff plastic	150 x 86 x 40 mm	470 g	prim. 1500 mm Schuko-stecker sec. 150 mm	max. 40°C	552-082-50



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel prim./sec. cable prim./sec.	Umgebungs-temperatur ta	Artikel-nummer ref.-No.
110 - 120 V oder 220 - 240 V / 50 - 60 Hz	24 Vdc 150 W / 6,25 A	Metall metal	199 x 110 x 50 mm	790 g	ohne without	max. 50°C	552-083-50